



**FAT** *Pipe*

# SD-WAN

## DATASHEET

**FatPipe Networks**

3<sup>rd</sup> Floor, Ragula Tech Park, Type II/16, Dr. VSI Estate (Phase 1), Thiruvanniyur, Chennai - 600 041 India  
www.fatpipeinc.com • info@fatpipeinc.com • Tel: +91 44 6670 7200

## FatPipe SD-WAN Solution:



- Seamless session failover in sub-seconds for session continuity using our patented technology. Ensuring clear and superior VoIP and video traffic.
- Granular data/session prioritization over multiple carrier lines.
- Selective encryption across the overlay fabric, not “double encryption” (which impedes session performance). FatPipe holds a patent on this technology.
- FatPipe architecture ensures that even if a remote Orchestrator is unavailable due to outages, the local boxes will continue to operate and transmit data efficiently.
- FatPipe load balances on Layer 3, and is compatible and future proofed for IoT, Layer 2 fabric, etc.
- Single pane of glass management.

## SD-WAN for HQ/Branch Site Redundancy & Load Balancing:

- **Deploy FatPipe SD-WAN solution** into network, to pass traffic on all available links.
- **Load Balance traffic** on all available paths and Automatic Failover to additional lines, in case of link failure, ensures uninterrupted service availability. All lines in active/active state.
- **Internet circuits at HQ and all sites with FatPipe appliances can now be used as failover for DIA circuits**, with secure transmission over public connections, with FatPipe patented MPsec encryption.
- **Provide for fast turn on of branch connectivity to main site/DCs**, using whatever Internet circuits are available (DIA, MPLS, Ethernet, broadband, cable, wireless, microwave, satellite, etc.).
- **Enable Orchestrator with Central Policy Propagation** to centrally control WANs and easily manage branches and branch deployments.
- **Branch appliances “phone home” for auto configurations** and policy-based routing rules.
- **Zero downtime is assured** as long as one link at the site is up and running.
- **IPSec tunnels terminate at the appliance for VPN functionality.**
- **Active link monitoring** for available bandwidth, latency, jitter and packet loss allows FatPipe to send traffic on the best path with better characteristics.
- **Prioritize outbound sessions** with FatPipe policy-based routing, ensuring high priority sessions have the required bandwidth.
- **Granular control of VoIP, Video, Skype, Lync, etc.** –with multiple options to define an application. (Source/Destination IP, ADS user, Source/Destination Port, Protocol, Pre-classified DSCP markers.)
- **Fail-to-Wire configuration**, in highly unlikely event of component/unit failure. Optional HA Paired units.

## Multi-Line WAN Aggregation:

- **Sub-Second Stateful VoIP Failover.** Patented technology fails VoIP traffic over in a sub second without dropping the call. With FatPipe, VoIP and other traffic are sent over ONE line only, and if that line fails, the data automatically fails over to another other line instantly. (Other vendors will send the same VoIP traffic over two lines, and whichever data reaches first is selected. Duplicating VoIP traffic causes clogging and inefficient traffic flow for offices that handle multiples of calls being placed simultaneously, or PBX and cloud services.)
- **Stateful Sub-Second Session Failover.** Patented technology works similarly for all data traffic and is especially valuable for companies that use Oracle and SAP. FatPipe automatically fails over all data sessions without dropping them when a line fails. This is important when production monitoring data is transmitted live. If a line fails in the middle of a transaction, the transaction is failed over without causing a loss of data.
- **True Outbound Load Balancing**, rather than just placing data session on two lines. Maximizes the data traffic and speeds up data transmission resulting in better ROI.
- **Rotating IP address Support**, Usually ISP lines with rotating/dynamic IP addresses are less expensive, and so small branches may be able to use them cost effectively.
- **Multiple Orchestrator Options**, can be in-band (on the customer’s networks for security), Hosted (data center outside the customer’s network), or Cloud Hosted as a service. Depending on the customer security requirements.
- **Built-in Firewall** appliance to be a single box solution.
- **No Data Plane Backhaul**, data does not have to leave the network if desired/required.
- **Threshold-Based Session Failover**, - based upon variable parameters (latency, jitter, packet loss) that you apply and set for specific applications (VoIP, Skype, Salesforce, O365, e.g.) to ensure the session follows the best path for that application.

## Visibility

- FatPipe WAN visibility, management and Reporting with Enterprise Dashboard View.

## Deployment

- Pre-deployment meetings, whiteboard sessions, and Visio diagrams to outline complete installation, deployment, and support.
- Collaborated efforts on staging, infrastructure configuration, testing, turn up and installations.

## Delivery Timelines

- Unit delivery: International shipping delivery timetables apply
- Installation: One-week turnaround.

### FatPipe SD-WAN Feature Matrix

Features	Standard	Real-Time	Enterprise
Outbound Load Balancing	✓	✓	✓
QoS	✓	✓	✓
IPSec VPN	✓	✓	✓
MPSec	✓	✓	✓
Sub-Second Failover	✓	✓	✓
Site-to-Site Overlay	✓	✓	✓
Split Tunneling / Local Internet Breakout	✓	✓	✓
Auto Config	✓	✓	✓
Firewall	✓	✓	✓
IPS, Geo Blocking	✓	✓	✓
Rotating IP Support	✓	✓	✓
Web Filter		✓	✓
Threshold Based Failover		✓	✓
Selective Encryption		✓	✓
Layer 3 Routing		✓	✓
Routing Protocol Support		✓	✓
Layer 7 PRR			✓
Full Mesh VPN			✓
Advanced VLAN Support			✓
L2 Routing			✓
Multicast Support			✓
Double NAT Support			✓
Advanced Routing – BGP, OSPF			✓
WAN Optimization Add-on license required			✓
Antivirus Add-on license required			✓
IDS Add-on license required			✓

Device Type	Long Mini 6	STD-1U (SFF)
<b>Hardware</b>		
<b>Form Factor</b>	1U	1U
<b>Power Supply</b>	Single	Single / Dual (Optional)
<b>CPU</b>	Intel Celeron 3865u 1.8GHz Dual Core with AESNI or Equivalent	Intel Pentium 4405U 2.1GHz Dual Core with AESNI or Equivalent
<b>RAM</b>	8 GB	16 GB
<b>Data Storage (SSD)</b>	128 GB	256 GB
<b>Included Ports</b>	6	6
<b>Optional Ports</b>	N/A	N/A
<b>Max. Ports</b>	6 (6 Port Gbe Onboard)	6 (6 Port Gbe Onboard)
<b>Max. WAN Ports</b>	5	5
<b>Expansion Slots</b>	0	0
<b>USB Ports</b>	2	2
<b>System Preferences</b>		
<b>Operating System</b>	64 Bit	64 Bit
<b>Max Throughput</b>	100 Mbps	1 Gbps
<b>High Availability (Hardware)</b>	Active / Standby	Active / Standby
<b>High Availability (Links)</b>	Active / Active	Active / Active
<b>Dimensions</b>		
<b>HW Dimensions (W x L x H)</b>	17.2" x 5" x 1.75"	16.9" x 11" x 1.75"
<b>Shipping Weight</b>	6 lbs	10 lbs
<b>Rack Mountable</b>	Yes	Yes
<b>Mounting Rail Kit</b>	Yes	Yes
<b>Environment</b>		
<b>Power Required</b>	100–240V AC, 50–60 Hz	100–240V AC, 50–60 Hz
<b>Power Consumption (Average)</b>	AC to DC 60W Max	AC to DC 60W Max
<b>Operating Temperature</b>	-10 - 60 deg C	-10 - 60 deg C
<b>Non - Operating Temperature</b>	-20 - 70 deg C	-20 - 70 deg C
<b>Humidity</b>	5% - 95% non-condensing	5% - 95% non-condensing
<b>Forced Airflow</b>	Front to Back	Front to Back